34E10

Series 3 Electric Strike 12V DC 5,800N Fail-Safe

Technical Data

Function	Fail-Safe
Operation	Normally Open (Fail-Safe)
Resistance to forced entry	5,800 N
Endurance Rating (Cycles)	200,000
Operating Temperature	-25ºC – +70ºC
Sound Level DC (at 50 cm)	5 dBA
Latch Spring Force	17-18 N
Door Opening Direction (DIN 107)	DIN R / DIN L
Vertical and Horizontal Installation	Yes
Strike Fixing Distance	52.5 mm
Height (Z)	71 mm
Width (X)	20.1 mm
Depth (Y)	28 mm
Keeper	Adjustable
Radian Keeper	External
Keeper Movement	34º
Keeper Depth	6.7 mm
Keeper Adjustment	3 mm

Connection



Product Certificates

Regulations	(UE) 305/2011
Standards	EN 14846:2008
EMC Directive	2014/30/UE
RoHS Directive	2011/65/UE
REACH Regulation	1907/2006

Electrical Data (at 20°C)

Coil	E
Nominal Voltage	12V DC
Rated Resistance	42 Ω
Duty Cycle (%ED)	100% ED
Transient Voltage Suppressor (TVS)	Yes
PCB Hardware Version	PCBA0000001

Patents

EP4001559A1, EP4206424A1, EP4239147A1, ES1057347, ES1158664U

Consumption (Tables showing relation between Tension (Vin), Consumption (A) and Preload Force (N))

Alternating Current (AC)

Vin (AC)	Initial				Holding
	C0(A)[1]	C1(A)[2]	DIN L (N)[4]	DIN R (N)[5]	C2(A)[3]
6	—	—	—	—	—
8	—	—	—	—	—
9	—	—	—	—	—
10	—	—	—	—	—
12	—	—	—	—	—
14	—	—	—	—	—
16	—	—	—	—	—
22	—	—	—	—	—
24	—	—	—	—	—
28	—	—	—	—	—
30	—	—	—	—	—

Direct Current (DC)

Vin (DC)	Initial				Holding
	C0(A)[1]	C1(A)[2]	DIN L (N)[4]	DIN R (N)[5]	C2(A)[3]
6	—	—	—	—	—
8	—	—	—	—	—
9	—	—	—	—	—
10	—	—	—	—	—
12	0.26	0.26	—	—	0.26
14	—	—	—	—	—
16	—	—	—	—	—
22	—	—	—	—	—
24	—	—	—	—	—
28	—	—	—	—	—
30	—	—	—	—	—

[1] C0: Peak current. [2] C1: Initial Consumption. [3] C2: Holding Consumption. [4,5] Preload Force in Newtons (N) DIN L, DIN R (With preload, the strike processes the opening in under 1 second).
The table shows the test values at a temperature of 20°C; any variation in this condition will affect both the power consumption and the holding force of the electric strike. Consumption deviation of ±7% due to ohmic tolerance of coil.

Openers & Closers S.L.
Calle Agricultura 17, nave 12, Sant Feliu de Llobregat, 08980 Barcelona, Spain
+34 934 080 515 | tech@openers-closers.com

OPENERS & CLOSERS makes every possible effort to ensure that the information provided in this document and in the products and services offered is accurate and up-to-date. However, the total accuracy and reliability of the information provided cannot be guaranteed.